

BO PRESS – 80 g/m²

MWC PAPER

Our BO PRESS paper is recommended for high demand magazine printing and tabloids.

It has a good opacity/brightness ratio.

TYPICAL END USES	PRINTING METHODS	FINISH	COLOR PROFILE
Mail order catalogues Travel brochures Multicolour magazines Flyer	HSWO	Gloss	FOGRA 46

TECHNICAL SPECIFICATIONS

		L*a*b* PROFILE	
		L* 90	a* 0.6 b* -4.0
Grammage	ISO 536	g/m ²	80
Brightness	ISO 2470, D65/10°	%	82
CIE Whiteness	ISO 11476, C/2°	%	80
Opacity	ISO 2471	%	96
Gloss	ISO 8254-1	%	56
Caliper	ISO 534	µm	71
Bulk	ISO 534	cm ³ /g	0.89
Smoothness	PPS 1MPa, ISO 8791-4	µm	1.3

REELS SPECIFICATIONS

Core	Total TRIM Area	Width	Diameters
76 mm	5.240 mm	Min: 40 cm - Max.: 196 cm	Min.: 100 cm - Max.: 120 cm

ENVIRONMENT	CERTIFICATES	PRODUCER
Bleached Chemical Pulp	ISO 14001	Arapoti Mill
Renewable Fiber	ISO 9001	
Recyclable Paper	OHSAS 18001	
Recyclable Packaging Materials	FSC® CoC	
	PEFC™ CoC	

STORAGE AND HANDLING

- Store the paper in a controlled area at maximum 50% relative humidity and temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilization period in the print room.
- Open the protective wrapping only at the moment of use.