

FORTRESS CUPSTOCK- POLY CTD DATA SHEET

Grade: 2143

Description: FORTRESS CS 16.3PT SHRIMP BOX

Nominal Basis Weight: 189.4Lbs./3,000 Sq. Ft.

308 GSM

Uncoated Basestock Grade: 1356 FORTRESS CS 16.3PT PA

Description			Uncoated	Coated	
Basis Weight, T411					
		Lbs. /3000 Sq. Ft.	180.0	194.4	
		GSM	293.0	316.4	
Caliper, T410					
		.001 inch	16.3	17.6	
		mm	0.414	0.447	
Stiffness, Taber V-5					
mNm - MD	17.71	g-cm - MD	180.5		
mNm - CD	7.70	g-cm - CD	78.5		
Moisture, % T412					
			7.1		
Smoothness, Sheffield Units T538					
		PS	200.0		
Elongation, % T404					
		MD	37.2		
		CD	36.7		
Bond, Lb - Force/msqin T833					
			90.0		
Brightness, % T452					
			84.0		
Side 1 - Resin film weight					
		Lbs. /3000 Sq. Ft. GSM		7.2 LDPE 11.7 High Gloss	Print Side Treated
Side 2 - Resin film weight					
		Lbs. /3000 Sq. Ft. GSM		7.2 LDPE 11.7 Matte	Non-Print Side Non Treated

Values are grade targets for uncoated "as made" board unless specified otherwise. Coated caliper is calculated, not an actual measurement. Values are subject to revision without notice.